



藝林機械五金有限公司

IKLIM HARDWARE & MACHINERY SDN. BHD.

(No. Syarikat: 22456-W)

No. 23, Jalan 8/91, Taman Shamelin Perkasa, 56100 Cheras, Kuala Lumpur.

Tel: 603-92848333, 92848411, 92848172, 92847890 Fax: 603-9282 3685

Website: www.iklim.com.my E-mail: ihmsb@po.jaring.my.

KBZ Submersible Dewatering Pump

Features :

- 1) The body of motor & pump is made of rigid cast iron for long-lasting durability.
- 2) Greatly increased max. Submersion depth due to m.seal resistant to high pressure 0.5Mpa)
- 3) Semi-open impeller made of high chrome alloy match with wear plate (ductile iron) achieves superior durability.
- 4) Effective motor cooling due to discharge channel cast as part of the motor housing. Space economy by a top outlet.
- 5) Discharge 50mm(2") to 150mm(6"), motor 1.5kw(2hp) to 15kw(20hp)
- 6) Hermerically sealed motor equipped build-in thermal protection.
- 7) Capacity up to 155m³ /h. Cable:length 8m
- 8) Water temperature up to 40°C. Max. water depth: 50m



Model	Motor	Max. Capacity	Max. Head	Outlet	Impeller Passage	Packing Dimension	Weight
	HP	m ³ /min	m	mm	mm	mm	Kg
KBZ21.5	2	0.45	22	50	8.5	585x270x270	37.5
KBZ22.2	3	0.55	26	50	8.5	585x270x270	39
KBZ23.7	5	0.55	34	50	8.5	685x325x300	65
KBZ31.5	2	0.67	14.5	80	8.5	585x270x270	34.5
KBZ32.2	3	0.92	19	80	8.5	585x270x270	39
KBZ33.7	5	0.92	29	80	8.5	685x325x300	65
KBZ35.5	7.5	1.25	34	80	8.5	725x355x370	84
KBZ43.7	5	1.5	18.5	100	8.5	685x325x300	66
KBZ45.5	7.5	1.75	23	100	8.5	725x355x370	85
KBZ47.5	10	1.4	40	100	11.5	805x365x390	114
KBZ411	15	1.4	48.5	100	11.5	855x415x440	140
KBZ67.5	10	2.08	31	150	19.5	835x365x390	114
KBZ611	15	2.45	32	150	19.5	855x415x440	143
KBZ615	20	2.6	40	150	19.5	895x415x440	156

**** Specification are subject to change without prior notice ****